



OBJT2.E206440

Single- and Multi-layer Insulated Winding Wire - Component

[Page Bottom](#)

Single- and Multi-layer Insulated Winding Wire - Component

[See General Information for Single- and Multi-layer Insulated Winding Wire - Component](#)

FURUKAWA ELECTRIC CO LTD


E206440

MAGNET WIRE DIV

2-2-3 MARUNOUCHI

CHIYODA-KU, TOKYO 100-8322 JAPAN

Cat. No.	Insulation Type	TIW Conductor Size Range	Temp Class °C	Rated Volts UL 60950-1 V peak	Rated Volts UL 60601-1 V rms
FSX-B	Basic	0.11 - 0.19 mm	130(B)	354	-
FSX-E, SX-E	Basic	40 - 29 AWG	120(E)	354	-
FWX-E	Supplementary	40 - 29 AWG	120(E)	354	-
TEX-BS	Reinforced	32 - 18 AWG	130(B)	1410	-
TEX-E, TEX-EA	Reinforced	32 - 18 AWG	130(B)	1410	-
TEX-ECEW3	Reinforced	33 - 19 AWG	130(B)	1410	-
TEX-ELZ	Reinforced	Cross-Section Area - 0.055mm ² - 0.495mm ²	130(B)	1410	-
TEX-FR	Reinforced	32 - 18 AWG	155(F)	1410	-
TEX-FS	Reinforced	32 - 18 AWG	155(F)	1410	-

Marking: Company name, material designation and the Recognized Component Mark,  on the smallest unit container in which the product is packaged, spool, or on a tag attached to the end of the wire.

[Last Updated](#) on 2016-10-24[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".